

NOCTIS MAX 2

SLI029078CW_PW

Floodlight NOCTIS MAX 2, with a power of 100 W, high light efficacy 100 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with a cold light (6000K). Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



IP65

IK08



Power	100 W
Luminous flux*	10000 lm (120°)
Colour of light	CW
IK	08

Voltage	230 V
Colour temperature	6000 K
Beam angle	85 °
Degree of protection (IP)	IP65

Technical data

Code	SLI029078CW_PW
Power	100 W
Nominal current	430 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	10000 lm (120°)
Luminous flux**	10000 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	6000 cd
Colour temperature	6000 K
Colour of light	CW
Beam angle	85 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	264x218x35 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	300 pcs.
Gross weight (1 pcs.)	0.85 kg

Related documents

 User manual Declaration of Conformity

