

NOCTIS MAX 2

SLI029080NW_PW

Floodlight NOCTIS MAX 2, with a power of 200 W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



IP65

IK08



Power	200 W
Luminous flux*	19000 lm (120°)
Colour of light	Neutral white
IK	08

Voltage	230 V
Colour temperature	4000 K
Beam angle	85 °
Degree of protection (IP)	IP65

Technical data

Code	SLI029080NW_PW
Power	200 W
Nominal current	860 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	19000 lm (120°)
Luminous flux**	19000 lm (360°)
Lamp efficacy	95 lm/W
Luminous intensity	11900 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	85 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	346x286x40 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	200 pcs.
Gross weight (1 pcs.)	1.56 kg

Related documents

 User manual Declaration of Conformity

