

ALGINE BACKLIGHT

SLI035096NW_PW

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 125 lm/W. It is made of high-quality components, supported by a 5-year warranty. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 90° gives directional light so that selected objects or surfaces can be better exposed. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	40 W	Voltage	230 V
Luminous flux*	5000 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	90 °
UGR	<19	Degree of protection (IP)	IP40

Technical data

Code	SLI035096NW_PW
Power	40 W
Nominal current	170 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.97
Useful luminous flux*	5000 lm (360°)
Luminous flux	4400 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
UGR	<19
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum, steel
Degree of protection (IP)	IP40
Colour	White
Dimension (AxBxC)	620x620x32 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	montaż ramka 70 mm lub sufit armstrong ,

Logistics data

Bulk packaging	6 pcs.
Quantity per pallet	72 pcs.
Gross weight (1 pcs.)	1.26 kg

*applies to the LED source used

Related documents



 Declaration of
Conformity