

# SHIFT NANO LINE M

WLD+80005

SYSTEM SHIFT NANO - LINE M LINEAR TRACKLIGHT 600X12X30MM 20W 100DEG WHITE 5Y WARRANTY



Power **20 W**  
Colour temperature **3000 K**  
Beam angle **100 °**

Voltage **48 V**  
Colour of light **WW**  
Degree of protection (IP) **IP20**

## Technical data

|                              |                |
|------------------------------|----------------|
| Code                         | WLD+80005      |
| Power                        | 20 W           |
| Nominal current              | 430 mA         |
| Voltage                      | 48 V           |
| Energy consumption           | 20 kWh/1000h   |
| Frequency                    | DC Hz          |
| Protection class             | III            |
| Power factor                 | 1              |
| Useful luminous flux*        | 2085 lm (360°) |
| Luminous flux**              | 650 lm (360°)  |
| Lamp efficacy                | 104 lm/W       |
| Colour temperature           | 3000 K         |
| Colour of light              | WW             |
| Beam angle                   | 100 °          |
| RA                           | >90            |
| Light source included        | Yes            |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | No             |
| Working temperature range    | -20 to +40 °   |
| Lifespan                     | 50000 h        |
| Housing material             | Aluminum       |
| Degree of protection (IP)    | IP20           |
| Colour                       | White          |
| Dimension (AxBxC)            | 600x12x30 mm   |
| For use                      | Inside         |
| Assembly method              | on track 48V   |
| Application                  | Inside         |
| Made in                      | PRC            |

## Logistics data

|                       |           |
|-----------------------|-----------|
| Bulk packaging        | 50 pcs.   |
| Gross weight (1 pcs.) | 0.2569 kg |

## Related documents

 User manual Declaration of Conformity

